

SIDEWALK

SIDEWALK

SIDEWALK

SIDEWALK

"No parking" signs must be placed MINIMUM 24 Hours in advance.

No parking signs wording must match either #1 or #2 below:

#1 = 24 hours: "No parking anytime TOW AWAY ZONE at all times"

or

#2 = Limited: "No parking anytime TOW AWAY ZONE 7am TO 5pm"

\*No parking sign spacing is approximately 20 - 25 feet apart.

\*Contractor must resolve all local access and safety issues.


\*All barricades, cones, and signs must be in accordance with the latest edition of the Manual on Uniform Traffic Control Devices (MUTCD).

\*Flaggers must follow MUTCD guidelines. Flaggers must be certified and use and wear safety equipment as required.

100'  
100'



Minimum 12 ft. Travel Lane must be maintained at all times.



SIDEWALK

SIDEWALK

Cone Spacing: 25 ft. apart

Taper - 50-100 feet max

Sign Spacing to be approx. 100 feet apart for low-speed local streets (<35mph).

100'

100'



SIDEWALK

SIDEWALK



Do not block or encumber sidewalks at any time

Drawing Not to Scale

Indicate North On Plan



City and County of Denver Department of Transportation & Infrastructure

Street - Single Flagger Closure

Residential Streets Only

Revised 9/28/2022